

# POS Solutions

# BPD-100

## Customer Display

With interchangeable pole sections

It provides the user with different display heights from "tabletop" to full pole!

The customer Display uses a VFD (Vacuum Florescent Display) tube to display the brightest characters viewable from a wide angle!



SPECIFICATIONS	
CHARACTERISTICS	SPECIFICATIONS
Customer Display	Vacuum Fluorescent Display
Display Pattern	5 x 7 dot matrix
Brightness	350~700 cd/m2
Character	95 Alphanumeric & 32 International Characters
Dot Size (X x Y)	0.86 x 1.2 mm
Font Size	5.25(W) x 9.3(H)
Character Number	20 x 2 for 5 x 7 font
Command	BPD-100, EPSON POS D101, Aedex, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL
Language	USA, France, Germany, U.K., Sweden, Denmark I & II, Italy, Spain, Norway, Japan (Katakana), Slavonic, Russian, etc...
Pass-through	Pass-through function is standard
Dimension (Panel) (W x D x H)	220 x 50 x 86mm
Dimension (Support)	2 supports in package, Per support : 130mm 130mm x 2 = 260 mm (H)x 33 mm (dia)
Dimension (base)	217 mm (W) x 106 mm (D) x 20 mm (H)
Viewing Angle	Max. 90°
Horizontal Rotation	Max. 360°
Weight	About 0.55 Kg
Interface	RS-232 and USB

Photos for illustrative purposes only.



# POS Solutions

# BPD-100

## Customer Display

With interchangeable pole sections

It provides the user with different display heights from "tabletop" to full pole!

The customer Display uses a VFD (Vacuum Florescent Display) tube to display the brightest characters viewable from a wide angle!



SPECIFICATIONS	
CHARACTERISTICS	SPECIFICATIONS
Customer Display	Vacuum Florescent Display
Display Pattern	5 x 7 dot matrix
Brightness	350~700 cd/m2
Character	95 Alphanumeric & 32 International Characters
Dot Size (X x Y)	0.86 x 1.2 mm
Font Size	5.25(W) x 9.3(H)
Character Number	20 x 2 for 5 x 7 font
Command	BPD-100, EPSON POS D101, Aedex, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL
Language	USA, France, Germany, U.K., Sweden, Denmark I & II, Italy, Spain, Norway, Japan (Katakana), Slavonic, Russian, etc...
Pass-through	Pass-through function is standard
Dimension (Panel) (W x D x H)	220 x 50 x 86mm
Dimension (Support)	2 supports in package, Per support : 130mm 130mm x 2 = 260 mm (H)x 33 mm (dia)
Dimension (base)	217 mm (W) x 106 mm (D) x 20 mm (H)
Viewing Angle	Max. 90°
Horizontal Rotation	Max. 360°
Weight	About 0.55 Kg
Interface	RS-232 and USB

Photos for illustrative purposes only.

